




MANGUERAS DE LAVADO, 1000 bar (Refuerzo acero, revestimiento de goma), para agua

COD	MANGUERA		Temp. (°C)	DN	Di. (mm)	De (mm)	Presión de trabajo (bar)	FS	Radio min. de curvatura (mm)	Peso (gr/m)	Largo Standard (m)	Niples
TB4SP08P	Manguera waterblast D. 1/2" , WP.1100B, L=15m		-10 / +70	1/2"	13	25	1100	2,5	230	1130	15	M-G-NPT
TB4SP12P	Manguera waterblast D. 3/4" , WP.1000B, L=15m		-10 / +70	3/4"	19	32	1000	2,5	250	1750	15	M-NPT



MANGUERAS DE LAVADO, 1000 bar (Refuerzo + acero, revestimiento de uretano) para agua

COD	MANGUERA		Temp. (°C)	DN	Di. (mm)	De (mm)	Presión de trabajo (bar)	FS	Radio min. de curvatura (mm)	Peso (gr/m)	Largo Standard (m)	Niple Manguera
JP47003	Manguera Jet Power 5/16"		-40 / +55	5/16"	8,0	16,0	1000	2,5	50	292	15	M24 X 1,5 FS
JP57001	Manguera Jet Power 3/8"		-40 / +55	3/8"	9,7	18,8	1120	2,5	90	389	15	M24 X 1,5 FS
JP67003	Manguera Jet Power 1/2"		-40 / +55	1/2"	12,0	25,2	1000	2,5	150	516	15	M24 X 1,5 FS
UHP2035	Manguera UHP 2033 d.5/16"		-30 / +70	5/16"	7,9	15,4	1200	2,5	100	370	15	M24 X 1,5 FS
UHP2033	Manguera UHP 2035 d.1/2"		-30 / +70	1/2"	12,8	22,1	1040	2,5	140	700	15	M24 X 1,5 FS

MANGUERAS DE LAVADO, UHP (Refuerzo acero, revestimiento de uretano) para agua

COD	MANGUERA	Imagen	Temp. (°C)	DN	Di. (mm)	De (mm)	Presión de trabajo (bar)	FS	Radio min. de curvatura (mm)	Peso (gr/m)	Largo Standard (m)	Niple Manguera
UHP 2261	Manguera UHP 2261 D. 3/16", 6 espirales		-40 / +55	3/16"	4,8	13,2	3050	2,3	210	687	15	especificar
UHP 2263	Manguera UHP 2263 D. 5/16", 6 espirales		-40 / +55	5/16"	7,6	19,7	3050	2,3	250	1.087	15	especificar
UHP 2265	Manguera UHP 2263 D. 1/2", 6 espirales		-40 / +55	1/2"	12,8	26,0	2500	2,5	350	1.782	15	especificar
UHP 2281	Manguera UHP 2281 D. 3/16", 8 espirales		-40 / +55	3/16"	4,7	16,0	3800	2,2	230	783	15	especificar
UHP 2283	Manguera UHP 2283 D. 5/16", 8 espirales		-40 / +55	5/16"	7,6	22,0	3800	2,4	300	1.519	15	especificar
UHP 2285	Manguera UHP 2285 D. 1/2", 8 espirales		-40 / +55	1/2"	12,8	28,7	3010	2,1	350	2.350	16	especificar

FLEXIBLES PARA DES OBSTRUCCION EN ALTA PRESIÓN (> 1000 BAR) (Refuerzo acero, revestimiento de uretano) para agua

COD	MANGUERA	Imagen	Temp. (°C)	DN	Di. (mm)	De (mm)	Presión de trabajo (bar)	FS	Radio min. de curvatura (mm)	Peso (gr/m)	Largo Standard (m)	Niple Flexible
JP17003	Flexible des obstructor Jet Power 1/8"		-40 / +55	1/8"	3,6	11,2	1120	2,5	25	180	15	1/8" NPT(M)
JP37003	Flexible des obstructor Jet Power 1/4"		-40 / +55	1/4"	6,4	14,5	1120	2,5	40	253	15	1/4" NPT(M)
JP47003	Flexible des obstructor Jet Power 5/16"		-40 / +55	5/16"	8,0	16,0	1000	2,5	50	292	15	1/4" NPT(M)
JP57003	Flexible des obstructor Jet Power 3/8"		-40 / +55	3/8"	9,7	18,8	1120	2,5	90	389	15	3/8" NPT(M)
JP67003	Flexible des obstructor Jet Power 1/2"		-40 / +55	1/2"	12,0	25,2	1000	2,5	150	516	15	1/2" NPT(M)
UHP1022	Flexible UHP2022, D 3/16", WP 1050, 2x1/8" NPT(M), L=15m		-30 / +70	3/16"	5,2	9,9	1040	2,5	90	152	15	1/8" NPT(M)
UHP1022	Flexible UHP2022, D 1/4", WP 1050, 2x1/4" NPT(M), L=15m		-30 / +70	1/4"	6,4	11,5	1040	2,5	110	207	15	1/4" NPT(M)
UHO2023	Flexible UHP2023, D 5/16", WP 1050, 2x1/4" NPT(M), L=15m		-30 / +70	5/16"	7,9	13,7	1040	2,5	130	251	15	1/4" NPT(M)
UHO2034	Flexible UHP2034, D.3/8", WP 1050, 2x3/8" NPT(M), L=15m		-30 / +70	3/8"	9,9	18,2	1100	2,5	120	520	15	3/8" NPT(M)
UHP2035	Flexible UHP2035, D.1/2", WP 1050, 2x1/2" NPT(M), L=15m		-30 / +70	1/2"	12,8	22,1	1040	2,5	140	700	15	1/2" NPT(M)